



EPrem Cabinets & Counters with LF28 Controller



Service Manual



ISO 14001



ISO 9001



Contents

Environmental Management Policy	1
Disposal Requirements	1
Cabinet & Counter Description	2
Controller Operation	2 to 3
Information Menu	4
Parameter Setting and Adjustment	4
Fuzzy Logic	4 to 5
Controller Electrical Connections	5
Probe Resistance Values	5
Parameters Cabinets & Counters	6 to 12
Technical Specification	13 to 14
Wiring Diagrams	15 to 16

Environmental Management Policy for Service Manuals and Duets.

Product Support and Installation Contractors

Foster Refrigerator recognises that its activities, products and services can have an adverse impact upon the environment.

The organisation is committed to implementing systems and controls to manage, reduce and eliminate its adverse environmental impacts wherever possible, and has formulated an Environmental Policy outlining our core aims. A copy of the Environmental Policy is available to all contractors and suppliers upon request.

The organisation is committed to working with suppliers and contractors where their activities have the potential to impact upon the environment. To achieve the aims stated in the Environmental Policy we require that all suppliers and contractors operate in compliance with the law and are committed to best practice in environmental management.

Product Support and Installation contractors are required to:

1. Ensure that wherever possible waste is removed from the client's site, where arrangements are in place all waste should be returned to Foster Refrigerator's premises. In certain circumstances waste may be disposed of on the clients site; if permission is given, if the client has arrangements in place for the type of waste.
2. If arranging for the disposal of your waste, handle, store and dispose of it in such a way as to prevent its escape into the environment, harm to human health, and to ensure the compliance with the environmental law. Guidance is available from the Environment Agency on how to comply with the waste management 'duty of care'.
3. The following waste must be stored of separately from other wastes, as they are hazardous to the environment: refrigerants, polyurethane foam, oils.
4. When arranging for disposal of waste, ensure a waste transfer note or consignment note is completed as appropriate. Ensure that all waste is correctly described on the waste note and include the appropriate six-digit code from the European Waste Catalogue. Your waste contractor or Foster can provide further information if necessary.
5. Ensure that all waste is removed by a registered waste carrier, a carrier in possession of a waste management licence, or a carrier holding an appropriate exemption. Ensure the person receiving the waste at its ultimate destination is in receipt of a waste management licence or valid exemption.
6. Handle and store refrigerants in such a way as to prevent their emission to atmosphere, and ensure they are disposed of safely and in accordance with environmental law.
7. Make arrangements to ensure all staff who handle refrigerants do so at a level of competence consistent with the City Guilds 2078 Handling Refrigerants qualification or equivalent qualification.
8. Ensure all liquid substances are securely stored to prevent leaks and spill, and are **not** disposed of to storm drains, foul drain, surface water to soil.

DISPOSAL REQUIREMENTS

If not disposed of properly all refrigerators have components that can be harmful to the environment. All old refrigerators must be disposed of by appropriately registered and licensed waste contractors, and in accordance with national laws and regulations.

EPrem Cabinet and Counter Description

The EPrem range, so called as can save up to 50% on energy usage, comes in two formats, the Full Gastronorm and the Non-Gastronorm.

Both come with a choice of capacities and temperatures, the full format comes with 650x530 shelves whereas the Non-Gastronorm unit has a smaller shelf measuring 530x550.

The units are manufactured as a one piece shell with easy clean stainless steel exterior. Each conforms to the current legislation and exceeds the Montreal protocol by using zero ODP (ozone depleting substances) refrigerants and insulation. There is also the added option of having Hydrocarbon refrigerant.

Each unit's temperature is controlled by a microprocessor with digital temperature display. There are several temperature options available exceeding the Climate Class 5 operations by giving an ambient temperature to 43°C. Each temperature display is also easy to read with a wipe clean finish.

The standard form of refrigeration system in this unit is integrated with an air-cooled condensing unit that allows cooled air to circulate through the evaporator, via the fan into storage areas. It does this by distributing the refrigerant into the evaporator controlled by a capillary.

Remote systems are also available as an option, the difference being, the evaporator is controlled by an expansion valve instead of capillary.

Other points to be made on these units are that they have coated coils to prevent corrosion and to help prolong the refrigerators life. They have easily removable thermal breaks, giving easy access to the door frame heater.

Also all have a wide magnetic gasket that gives a positive door seal.

Cabinets come with an easily removable plug box and lid, while cabinets have an easy access condensing unit fitted on the side to make servicing that much easier.

Controller Operation

LF 28B2SE-B (00-555920) Controller.



LCD 5S controller display (00-555992)


Operation Guidelines

Initial Start Up.

Start Up & self Test: 

The indication is only displayed during the first three seconds following the mains electrical power being applied to the unit. During this period the controller performs a self-check.

Once the self-check has been completed  will be displayed.

Press and hold  for three seconds. The unit will start and the air temperature will be displayed.

Check temperature set point.

Important to note that the ability to increase and decrease the set point is not a function available to the user as the set point is fixed. To make adjustments to the set point it is necessary to access the parameter and alter SPL and SPH accordingly.

Check set point by briefly holding the  button

To increase set point press  +  until required temperature is displayed.

To decrease set point press  +  until required temperature is displayed.

Factory Temperature Set Point

Refrigerator +1°C to +4°C


Meat 0°C to 2°C.

Freezer -18°C to -21°C.

Exit from set up occurs after 10 seconds if no button is pressed.

Manual Defrost.

To initiate a manual defrost press and hold .  will be displayed release .

On completion of the defrost  will be displayed until the cabinet temperature is achieved and then it will revert to displaying the normal cabinet temperature.


Set Unit to Standby.

Press  display shows 

This indication is displayed while the unit is not operating but with mains power applied to the unit. This mode may be used for internal cleaning regimes and short periods when the unit is not required. For extended periods of inactivity the mains supply should be isolated.

Alarm and Warnings


High temperature alarm

 Will be displayed.

The alarm will sound but can be silenced by pressing any of the buttons, however it will return after the pre-set designated period. The unit returning to normal operating temperature will automatically cancel the alarm.

Possible Causes: Evaporator fan not working. Restricted airflow through airduct. Evaporator iced up. Compressor not working.


Low temperature alarm.


 Will be displayed.

The alarm will sound but can be silenced by pressing any of the buttons and the unit will continue to operate, however it will return after the pre-set designated period. The unit returning to normal operating temperature will automatically cancel the alarm.

Possible Causes: Controller faulty (not switching compressor off). Compressor secondary relay will not de-energise (low temperature models).

Door Open Alarm. (Only applies to cabinets fitted with door switches.)

 Will be displayed.


The alarm will sound but can be silenced by pressing 

The display will continue to display the alarm message until cancelled by shutting the door.

If the alarm cannot be cancelled by doing this call your Foster Authorised Service Company.

Possible Causes: Faulty door switch. Door left open for more than 5minutes.

High Pressure Alarm (Only applies to machines fitted with a condenser probe).


 Will be displayed

This alarm relate to the condenser which must be checked and cleaned at regular intervals the frequency being determined by site conditions.

The alarm will sound but can be silenced by pressing any of the buttons and the unit will continue to operate, however it will return after the pre-set designated period. The unit returning to normal operating temperature will automatically cancel the alarm.

Possible Causes: Condenser fan not working. Condenser blocked/ dirty. Condenser obstructed.

Air Temperature Probe Failure.


 Will be displayed.

The alarm will sound but can be silenced by pressing any button.

There is no further action that can be taken by the user in this instance. During this period the unit will continue to operate but have a reduced performance.

Action: Replace Probe.

Evaporator Temperature Probe Failure. (Automatic Defrost Cabinets Only)


 Will be displayed.

The alarm will sound but can be silenced by pressing any button.




There is no further action that can be taken by the user in this instance. During this period the unit will continue to operate satisfactorily, but this failure will have an effect on the defrost and therefore efficiency if allowed to continue.

Action: Replace Probe.


Information Menu

Pressing and releasing  activates the information menu. From this menu you can display the temperature relating to T1 (air probe), T2 (evaporator probe, if fitted) and T3 (condenser probe, if fitted). The maximum temperature (THI) and the minimum temperature (TLO) the cabinet has achieved since it was last re-set.

The total operating time of the condenser (CND), since it was last cleaned, and the keyboard status (LOC).

The information to be displayed can be selected sequentially by pressing  repeatedly or scrolling through the menu using the  or  buttons.

Once selected press  to display the value

Exit from the info menu by pressing  or is automatic after 6 seconds if no buttons are pressed.

To reset the temperature settings recorded in THI and TLO and the hours counted in CND, access the info menu



press  to display the value plus  simultaneously for resetting to be completed.

To check the LOC status scroll through to LOC, press  to display status – YES to lock keys. – NO to leave keys accessible.

NOTE: with the keys locked it is not possible to turn the unit off or ON or to check the set point

Parameter Setting and Adjustment


It is strongly advised that before adjusting any Service Parameters a thorough understanding of the following instructions should be obtained.

The parameters are accessed by pressing the following keys in succession  +  and keeping them pressed for 5 seconds.

After this period the first parameter 'SCL' will be displayed.

Press button  to pass from one parameter to the next and button  to go back.

Press  to display the value +  or  to change it.

Exit from set up is by pressing  or is automatic if no buttons are pressed for 30 seconds

Fuzzy Logic.

These are settings that maintain the temperature of the cabinet in a more energy efficient manner.

It works by controlling the evaporator fan/s, defrost and temperature in low usage times by transferring the operation to a second set of economy parameters.

When the cabinet is first switched On the economy settings control the operation of the temperature and will remain at those settings until the controller, by monitoring the door opening frequency and the air and evaporator temperatures, identifies a higher usage and switches over to the 11SM (2nd parameter set management).

When the economy settings are activated the cabinet temperature is allowed to rise to the setting (SP) setpoint [1]. This is set to a higher temperature setting to allow the air temperature to rise without having much of an impact on the product temperature.

In addition the fan/s will modulate (cycle for 30 seconds) as set in (FPC) evaporator fan On / Off Ratio.

The parameter is set at 1.

Changing the setting to 0 will have the fan running with the compressor. Set to 1 the fan will run for 30 seconds on and 60 seconds off. Set to 2 the fan will run for 60 seconds on and 60 seconds off and set to 3 the fan will run for 90 seconds on and 60 seconds off.

With FPC set to 1, 2 or 3 the fans will generate less heat into the cabinet therefore reduce the requirement of the condensing system.

NOTE:

Parameter FPC will only function with the parameter FTC set for YES. With FTC set to NO the fan will run all of the time apart from during defrost when it will be off during electric and hot gas defrost but on during a timed off cycle defrost.

Fan Operation.

The evaporator fan/s will run normally when the compressor is running but will commence cycling when the compressor is in the off cycle mode.

The fans will run without the compressor during timed off cycle defrost but will not run during hot gas or electric defrost.

For models that don't have door switches fitted the fuzzy logic will not function as the controller is unable to monitor door opening factors.

Auto Defrost operation.

The defrost frequency is determined by the usage of the machine.

In the economy mode it may not perform a defrost as by monitoring the air temperature, evaporator temperature and door opening factor it may decide that there is insufficient ice build up on the evaporator so defrosting is not required.

The parameter DFR (defrost frequency) is set for 3. The cabinet will perform at least 1 defrost per day and with the setting at 3 it has the potential to initiate up to 2 additional defrost in the economy mode.


Should the cabinet experience constant usage the controller will switch automatically to the second parameter

settings indicated by the controller LED adjacent to **II** illuminating, which could under circumstances of heavy usage initiate up to 6 defrosts per day.

The second parameter settings preceded by 11 will now be active,

It is important to note that during the first few days of operation the defrosting frequency may be at regular intervals but these will reduce as the controller monitors the operation.

Controller Electrical Connections



Probes

Air and Evaporator Probes

The air and evaporator probes are the same and are identified as T1 Air Probe and T2 Evaporator Probe. These are the K2 NTC thermistor type and are fully enclosed to make it completely waterproof and resilient to temperature variation within the limits of rapid cycling. The probe is capable of measuring temperature in excess of -30°C and 50°C with 1°K accuracy at 1°C and no more than 2°K at the upper and lower temperature ranges.

Probe temperature resistance values

°C	K ohm	°C	K ohm	°C	K ohm	°C	K ohm	°C	K ohm
-25	19.402	-15	11.644	5	4.571	15	2.987	25	2
-20	14.961	-10	8.133	10	3.682	20	2.437	40	1.143

F 28B2SE-B (00-555920) Controller Parameter lists

Parameter list for High Temperature cabinets including: -

EPREMB600H, EPREMG1100H, EPREMG1350H, EPREMG500H, EPREMG600H.

Also remote condensing unit models (R).

Parameter list for High Temperature counters including: -

EPREM1/2H, EREM1/3H, EPREM1/4H, EPREM2/2H, EPREM2/3H,

Also remote condensing unit models (R).

Note: For all counters adjust parameter 'DS' to NO as door switches are not fitted to these models.

Mnem.	Definition	Min.	Max	Default	Dim.	HT
SCL	Readout scale	1°C; 2°C; °F		2	flag	2
SPL	Minimum setpoint [I]	-40	SPH	1	°C	1
SPH	Maximum setpoint [I]	SPL	40	3	°C	3
SP	Setpoint [I]	SPL	SPH	2	°C	2
HYS	Thermostat hysteresis [I]	0.1	10	3	°K	3
CRT	Minimum compressor rest time	0	30	2	min.	2
CT1	Compressor run with T1 failure	0	30	7	min.	7
CT2	Compressor stop with T1 failure	0	30	3	min.	3
2CD	Start delay 2nd compressor	0	120	0	sec.	0
DFR	Defrost frequency / 24h	0	24	2	1/24h	2
DLI	Defrost end temperature	-40	40	20	°C	20
DTO	Maximum defrost duration	1	120	20	min.	20
DTY	Defrost type	OFF; ELE; GAS		OFF	flag	OFF
DRN	Drain down time	0	30	2	min.	2
DDY	Defrost display control	0	60	10	min.	10
FID	Fan activity during defrost	NO	YES	YES	flag	YES
FDD	Fan re-start delay temperature	-40	40	0	°C	0
FTO	Evaporator fan maximum time-out	0	120	3	min.	3
FTC	Evaporator fan timed control	NO	YES	YES	flag	YES
FT1	Fan stop delay	0	180	15	sec.	15
FT2	Timed fan stop	0	30	2	min.	2
FT3	Timed fan run	0	30	1	min.	1
ATL	Low alarm differential	-12	0	-5	°K	-5
ATH	High alarm differential	0	12	5	°K	5
ATD	Alarm Temperature Delay	0	120	90	min.	90
AHT	Condenser Alarm Temperature	0	75	60	°C	60
AHM	Condenser high temp. alarm operation	NON; ALR; STP		NON	flag	NON
ACC	Condenser cleaning period	0	52	0	wks	0
HDS	Sensitivity function eco / heavy duty	1	5	3	flag	3
IISM	2nd parameter set switching mode	NON; MAN; HDD; DI2		HDD	flag	HDD
IISL	Minimum 2nd temp. set	-40	IISH	1	°C	1
IISH	Maximum 2nd temp. set	IISL	40	3	°C	3
IISP	Effective 2nd temperature set point	IISL	IISH	1	°C	1
IIHY	Hysteresis 2nd temperature set	0.1	10	3	°K	3
IIFT	Evap. fan timed control in mode 2	NO	YES	NO	flag	NO
IIDF	Defrost Frequency / 24h in mode 2	0	24	4	1/24h	4
SB	Button 0/1 enabling	NO	YES	YES	flag	YES
DS	Door switch enabling	NO	YES	YES	flag	YES
CSD	Compressor stop delay from door opening	0	30	1	min.	1
ADO	Door alarm delay	0	30	8	min.	8
D12	Function digital input D12	NON; HPS; IISM; RDS		NON	flag	NON
LSM	Light switch mode	NON; MAN; DOR		NON	flag	NON
OAU	Control of AUX output	NON; 0-1; LGT; 2CU; 2EU; ALR		NON	flag	NON
OS1	T1 (air) probe offset	-12	12	0	°K	0
T2	T2 (evap.) probe enabling	NO	YES	NO	flag	NO
OS2	T2 (evap.) probe offset	-12	12	0	°K	0
T3	T3 (cond.) probe enabling	NO	YES	NO	flag	NO
OS3	T3 (cond.) probe offset	-12	12	0	°K	0
T4	T4 (aux.) probe enabling	NON; 2CU; 2EU		NON	flag	NON
OS4	T4 (aux.) probe offset	-12	12	0	°K	0
TLD	Delay for min./max. temp storage	1	30	5	min.	5
SIM	Display slowdown	0	100	3	exp.	3

ADR	Unit peripheral address	1	255	1	exp.	1
------------	-------------------------	---	-----	---	------	---

Parameter list for Low Temperature cabinets with hot gas defrost including: -
EPREMB600L, EPREMG1100L, EPREMG1350L, EPREMG500L, EPREMG600L.

Parameter list for Low Temperature counters with hot gas defrost including: -
EPREM1/2L, EPREM1/3L, EPREM1/4L, EPREM2/2L, EPREM2/3L,

Note: For all counters adjust parameter 'DS' to NO as door switches are not fitted to these models.

Mnem.	Definition	Min.	Max	Default	Dim.	LT Gas
SCL	Readout scale	1°C; 2°C; °F		2	flag	2
SPL	Minimum setpoint [I]	-40	SPH	1	°C	-21
SPH	Maximum setpoint [I]	SPL	40	3	°C	-19
SP	Setpoint [I]	SPL	SPH	2	°C	-19
HYS	Thermostat hysteresis [I]	0.1	10	3	°K	3
CRT	Minimum compressor rest time	0	30	2	min.	2
CT1	Compressor run with T1 failure	0	30	7	min.	7
CT2	Compressor stop with T1 failure	0	30	3	min.	3
2CD	Start delay 2nd compressor	0	120	0	sec.	0
DFR	Defrost frequency / 24h	0	24	2	1/24h	4
DLI	Defrost end temperature	-40	40	20	°C	20
DTO	Maximum defrost duration	1	120	20	min.	20
DTY	Defrost type	OFF; ELE; GAS		OFF	flag	GAS
DRN	Drain down time	0	30	2	min.	2
DDY	Defrost display control	0	60	10	min.	10
FID	Fan activity during defrost	NO	YES	YES	flag	NO
FDD	Fan re-start delay temperature	-40	40	0	°C	0
FTO	Evaporator fan maximum time-out	0	120	3	min.	3
FTC	Evaporator fan timed control	NO	YES	YES	flag	YES
FT1	Fan stop delay	0	180	15	sec.	15
FT2	Timed fan stop	0	30	2	min.	3
FT3	Timed fan run	0	30	1	min.	1
ATL	Low alarm differential	-12	0	-5	°K	-5
ATH	High alarm differential	0	12	5	°K	5
ATD	Alarm Temperature Delay	0	120	90	min.	90
AHT	Condenser Alarm Temperature	0	75	60	°C	60
AHM	Condenser high temp. alarm operation	NON; ALR; STP		NON	flag	NON
ACC	Condenser cleaning period	0	52	0	wks	0
HDS	Sensitivity function eco / heavy duty	1	5	3	flag	3
IISM	2nd parameter set switching mode	NON; MAN; HDD; DI2		HDD	flag	HDD
IISL	Minimum 2nd temp. set	-40	IISH	1	°C	-21
IISH	Maximum 2nd temp. set	IISL	40	3	°C	-21
IISP	Effective 2nd temperature set point	IISL	IISH	1	°C	-21
IIHY	Hysteresis 2nd temperature set	0.1	10	3	°K	3
IIFT	Evap. fan timed control in mode 2	NO	YES	NO	flag	NO
IIDF	Defrost Frequency / 24h in mode 2	0	24	4	1/24h	4
SB	Button 0/1 enabling	NO	YES	YES	flag	YES
DS	Door switch enabling	NO	YES	YES	flag	YES
CSD	Compressor stop delay from door opening	0	30	1	min.	1
ADO	Door alarm delay	0	30	8	min.	8
D12	Function digital input D12	NON; HPS; IISM; RDS		NON	flag	NON
LSM	Light switch mode	NON; MAN; DOR		NON	flag	NON
OAU	Control of AUX output	NON; 0-1; LGT; 2CU; 2EU; ALR		NON	flag	NON
OS1	T1 (air) probe offset	-12	12	0	°K	0
T2	T2 (evap.) probe enabling	NO	YES	NO	flag	YES
OS2	T2 (evap.) probe offset	-12	12	0	°K	0
T3	T3 (cond.) probe enabling	NO	YES	NO	flag	NO
OS3	T3 (cond.) probe offset	-12	12	0	°K	0
T4	T4 (aux.) probe enabling	NON; 2CU; 2EU		NON	flag	NON
OS4	T4 (aux.) probe offset	-12	12	0	°K	0
TLD	Delay for min./max. temp storage	1	30	5	min.	5
SIM	Display slowdown	0	100	3	exp.	3
ADR	Unit peripheral address	1	255	1	exp.	1

Parameter list for Low Temperature cabinets with electric defrost including: -
 EPREMB600L, EPREMG500L, EPREMG600L, EPREMG600L,

Parameter list for Low Temperature counters with electric defrost including: -
 EPREM1/2L, EPRO1/3L, EPREM1/4L, EPREM2/2L, EPREM2/3L,

Note: For all counters adjust parameter 'DS' to NO as door switches are not fitted to these models.

Mnem.	Definition	Min.	Max	Default	Dim.	LT Electric
SCL	Readout scale	1°C; 2°C; °F		2	flag	2
SPL	Minimum setpoint [I]	-40	SPH	1	°C	-21
SPH	Maximum setpoint [I]	SPL	40	3	°C	-19
SP	Setpoint [I]	SPL	SPH	2	°C	-19
HYS	Thermostat hysteresis [I]	0.1	10	3	°K	3
CRT	Minimum compressor rest time	0	30	2	min.	2
CT1	Compressor run with T1 failure	0	30	7	min.	7
CT2	Compressor stop with T1 failure	0	30	3	min.	3
2CD	Start delay 2nd compressor	0	120	0	sec.	0
DFR	Defrost frequency / 24h	0	24	2	1/24h	4
DLI	Defrost end temperature	-40	40	20	°C	20
DTO	Maximum defrost duration	1	120	20	min.	20
DTY	Defrost type	OFF; ELE; GAS		OFF	flag	ELE
DRN	Drain down time	0	30	2	min.	2
DDY	Defrost display control	0	60	10	min.	10
FID	Fan activity during defrost	NO	YES	YES	flag	NO
FDD	Fan re-start delay temperature	-40	40	0	°C	0
FTO	Evaporator fan maximum time-out	0	120	3	min.	3
FTC	Evaporator fan timed control	NO	YES	YES	flag	YES
FT1	Fan stop delay	0	180	15	sec.	15
FT2	Timed fan stop	0	30	2	min.	3
FT3	Timed fan run	0	30	1	min.	1
ATL	Low alarm differential	-12	0	-5	°K	-5
ATH	High alarm differential	0	12	5	°K	5
ATD	Alarm Temperature Delay	0	120	90	min.	90
AHT	Condenser Alarm Temperature	0	75	60	°C	60
AHM	Condenser high temp. alarm operation	NON; ALR; STP		NON	flag	NON
ACC	Condenser cleaning period	0	52	0	wks	0
HDS	Sensitivity function eco / heavy duty	1	5	3	flag	3
IISM	2nd parameter set switching mode	NON; MAN; HDD; DI2		HDD	flag	HDD
IISL	Minimum 2nd temp. set	-40	IISH	1	°C	-21
IISH	Maximum 2nd temp. set	IISL	40	3	°C	-21
IISP	Effective 2nd temperature set point	IISL	IISH	1	°C	-21
IIHY	Hysteresis 2nd temperature set	0.1	10	3	°K	3
IIFT	Evap. fan timed control in mode 2	NO	YES	NO	flag	NO
IIDF	Defrost Frequency / 24h in mode 2	0	24	4	1/24h	4
SB	Button 0/1 enabling	NO	YES	YES	flag	YES
DS	Door switch enabling	NO	YES	YES	flag	YES
CSD	Compressor stop delay from door opening	0	30	1	min.	1
ADO	Door alarm delay	0	30	8	min.	8
D12	Function digital input D12	NON; HPS; IISM; RDS		NON	flag	NON
LSM	Light switch mode	NON; MAN; DOR		NON	flag	NON
OAU	Control of AUX output	NON; 0-1; LGT; 2CU; 2EU; ALR		NON	flag	NON
OS1	T1 (air) probe offset	-12	12	0	°K	0
T2	T2 (evap.) probe enabling	NO	YES	NO	flag	YES
OS2	T2 (evap.) probe offset	-12	12	0	°K	0
T3	T3 (cond.) probe enabling	NO	YES	NO	flag	NO
OS3	T3 (cond.) probe offset	-12	12	0	°K	0
T4	T4 (aux.) probe enabling	NON; 2CU; 2EU		NON	flag	NON
OS4	T4 (aux.) probe offset	-12	12	0	°K	0
TLD	Delay for min./max. temp storage	1	30	5	min.	5
SIM	Display slowdown	0	100	3	exp.	3
ADR	Unit peripheral address	1	255	1	exp.	1

Parameter list for Meat Temperature cabinets with hot gas defrost including: -
EPREMG1350M, EPREMG600M.

Parameter list for Meat Temperature counters with hot gas defrost including: -
EPEM1/2M, EPREM1/3M, EPREM1/4M.

Note: For all counters adjust parameter 'DS' to NO as door switches are not fitted to these models.

Mnem.	Definition	Min.	Max	Default	Dim.	MT Gas
SCL	Readout scale	1°C; 2°C; °F		2	flag	2
SPL	Minimum setpoint [I]	-40	SPH	1	°C	-2
SPH	Maximum setpoint [I]	SPL	40	3	°C	0
SP	Setpoint [I]	SPL	SPH	2	°C	-1
HYS	Thermostat hysteresis [I]	0.1	10	3	°K	2
CRT	Minimum compressor rest time	0	30	2	min.	2
CT1	Compressor run with T1 failure	0	30	7	min.	7
CT2	Compressor stop with T1 failure	0	30	3	min.	3
2CD	Start delay 2nd compressor	0	120	0	sec.	0
DFR	Defrost frequency / 24h	0	24	2	1/24h	4
DLI	Defrost end temperature	-40	40	20	°C	20
DTO	Maximum defrost duration	1	120	20	min.	20
DTY	Defrost type	OFF; ELE; GAS		OFF	flag	GAS
DRN	Drain down time	0	30	2	min.	2
DDY	Defrost display control	0	60	10	min.	10
FID	Fan activity during defrost	NO	YES	YES	flag	NO
FDD	Fan re-start delay temperature	-40	40	0	°C	0
FTO	Evaporator fan maximum time-out	0	120	3	min.	3
FTC	Evaporator fan timed control	NO	YES	YES	flag	YES
FT1	Fan stop delay	0	180	15	sec.	15
FT2	Timed fan stop	0	30	2	min.	3
FT3	Timed fan run	0	30	1	min.	1
ATL	Low alarm differential	-12	0	-5	°K	-5
ATH	High alarm differential	0	12	5	°K	5
ATD	Alarm Temperature Delay	0	120	90	min.	90
AHT	Condenser Alarm Temperature	0	75	60	°C	60
AHM	Condenser high temp. alarm operation	NON; ALR; STP		NON	flag	NON
ACC	Condenser cleaning period	0	52	0	wks	0
HDS	Sensitivity function eco / heavy duty	1	5	3	flag	3
IISM	2nd parameter set switching mode	NON; MAN; HDD; DI2		HDD	flag	HDD
IISL	Minimum 2nd temp. set	-40	IISH	1	°C	-2
IISH	Maximum 2nd temp. set	IISL	40	3	°C	0
IISP	Effective 2nd temperature set point	IISL	IISH	1	°C	-2
IIHY	Hysteresis 2nd temperature set	0.1	10	3	°K	2
IIFT	Evap. fan timed control in mode 2	NO	YES	NO	flag	NO
IIDF	Defrost Frequency / 24h in mode 2	0	24	4	1/24h	4
SB	Button 0/1 enabling	NO	YES	YES	flag	YES
DS	Door switch enabling	NO	YES	YES	flag	YES
CSD	Compressor stop delay from door opening	0	30	1	min.	1
ADO	Door alarm delay	0	30	8	min.	8
D12	Function digital input D12	NON; HPS; IISM; RDS		NON	flag	NON
LSM	Light switch mode	NON; MAN; DOR		NON	flag	NON
OAU	Control of AUX output	NON; 0-1; LGT; 2CU; 2EU; ALR		NON	flag	NON
OS1	T1 (air) probe offset	-12	12	0	°K	0
T2	T2 (evap.) probe enabling	NO	YES	NO	flag	YES
OS2	T2 (evap.) probe offset	-12	12	0	°K	0
T3	T3 (cond.) probe enabling	NO	YES	NO	flag	NO
OS3	T3 (cond.) probe offset	-12	12	0	°K	0
T4	T4 (aux.) probe enabling	NON; 2CU; 2EU		NON	flag	NON
OS4	T4 (aux.) probe offset	-12	12	0	°K	0
TLD	Delay for min./max. temp storage	1	30	5	min.	5
SIM	Display slowdown	0	100	3	exp.	3
ADR	Unit peripheral address	1	255	1	exp.	1

Parameter list for Meat Temperature cabinets with electric defrost including: -
EPREMG1350M, EPREMG600M, EPREMG600M.

Parameter list for Meat Temperature counters with electric defrost including: -
EPREM1/2M, EPREM1/3M, EPREM1/4M.

Note: For all counters adjust parameter 'DS' to NO as door switches are not fitted to these models.

Mnem.	Definition	Min.	Max	Default	Dim.	MT Electric
SCL	Readout scale	1°C; 2°C; °F		2	flag	2
SPL	Minimum setpoint [I]	-40	SPH	1	°C	-2
SPH	Maximum setpoint [I]	SPL	40	3	°C	0
SP	Setpoint [I]	SPL	SPH	2	°C	-1
HYS	Thermostat hysteresis [I]	0.1	10	3	°K	2
CRT	Minimum compressor rest time	0	30	2	min.	2
CT1	Compressor run with T1 failure	0	30	7	min.	7
CT2	Compressor stop with T1 failure	0	30	3	min.	3
2CD	Start delay 2nd compressor	0	120	0	sec.	0
DFR	Defrost frequency / 24h	0	24	2	1/24h	4
DLI	Defrost end temperature	-40	40	20	°C	20
DTO	Maximum defrost duration	1	120	20	min.	20
DTY	Defrost type	OFF; ELE; GAS		OFF	flag	ELE
DRN	Drain down time	0	30	2	min.	2
DDY	Defrost display control	0	60	10	min.	10
FID	Fan activity during defrost	NO	YES	YES	flag	NO
FDD	Fan re-start delay temperature	-40	40	0	°C	0
FTO	Evaporator fan maximum time-out	0	120	3	min.	3
FTC	Evaporator fan timed control	NO	YES	YES	flag	YES
FT1	Fan stop delay	0	180	15	sec.	15
FT2	Timed fan stop	0	30	2	min.	3
FT3	Timed fan run	0	30	1	min.	1
ATL	Low alarm differential	-12	0	-5	°K	-5
ATH	High alarm differential	0	12	5	°K	5
ATD	Alarm Temperature Delay	0	120	90	min.	90
AHT	Condenser Alarm Temperature	0	75	60	°C	60
AHM	Condenser high temp. alarm operation	NON; ALR; STP		NON	flag	NON
ACC	Condenser cleaning period	0	52	0	wks	0
HDS	Sensitivity function eco / heavy duty	1	5	3	flag	3
IISM	2nd parameter set switching mode	NON; MAN; HDD; DI2		HDD	flag	HDD
IISL	Minimum 2nd temp. set	-40	IISH	1	°C	-2
IISH	Maximum 2nd temp. set	IISL	40	3	°C	0
IISP	Effective 2nd temperature set point	IISL	IISH	1	°C	-2
IIHY	Hysteresis 2nd temperature set	0.1	10	3	°K	2
IIFT	Evap. fan timed control in mode 2	NO	YES	NO	flag	NO
IIDF	Defrost Frequency / 24h in mode 2	0	24	4	1/24h	4
SB	Button 0/1 enabling	NO	YES	YES	flag	YES
DS	Door switch enabling	NO	YES	YES	flag	YES
CSD	Compressor stop delay from door opening	0	30	1	min.	1
ADO	Door alarm delay	0	30	8	min.	8
D12	Function digital input D12	NON; HPS; IISM; RDS		NON	flag	NON
LSM	Light switch mode	NON; MAN; DOR		NON	flag	NON
OAU	Control of AUX output	NON; 0-1; LGT; 2CU; 2EU; ALR		NON	flag	NON
OS1	T1 (air) probe offset	-12	12	0	°K	0
T2	T2 (evap.) probe enabling	NO	YES	NO	flag	YES
OS2	T2 (evap.) probe offset	-12	12	0	°K	0
T3	T3 (cond.) probe enabling	NO	YES	NO	flag	NO
OS3	T3 (cond.) probe offset	-12	12	0	°K	0
T4	T4 (aux.) probe enabling	NON; 2CU; 2EU		NON	flag	NON
OS4	T4 (aux.) probe offset	-12	12	0	°K	0
TLD	Delay for min./max. temp storage	1	30	5	min.	5
SIM	Display slowdown	0	100	3	exp.	3
ADR	Unit peripheral address	1	255	1	exp.	1

**Parameter list for Fish cabinets including: -
EPREMG1350F, PREMG600F.**

Note: For all counters adjust parameter 'DS' to NO as door switches are not fitted to these models.

Mnem.	Definition	Min.	Max	Default	Dim.	FT
SCL	Readout scale	1°C; 2°C; °F		2	flag	2
SPL	Minimum setpoint [I]	-40	SPH	1	°C	-1
SPH	Maximum setpoint [I]	SPL	40	3	°C	1
SP	Setpoint [I]	SPL	SPH	2	°C	0
HYS	Thermostat hysteresis [I]	0.1	10	3	°K	2
CRT	Minimum compressor rest time	0	30	2	min.	2
CT1	Compressor run with T1 failure	0	30	7	min.	7
CT2	Compressor stop with T1 failure	0	30	3	min.	3
2CD	Start delay 2nd compressor	0	120	0	sec.	0
DFR	Defrost frequency / 24h	0	24	2	1/24h	0
DLI	Defrost end temperature	-40	40	20	°C	20
DTO	Maximum defrost duration	1	120	20	min.	20
DTY	Defrost type	OFF; ELE; GAS		OFF	flag	OFF
DRN	Drain down time	0	30	2	min.	2
DDY	Defrost display control	0	60	10	min.	10
FID	Fan activity during defrost	NO	YES	YES	flag	YES
FDD	Fan re-start delay temperature	-40	40	0	°C	0
FTO	Evaporator fan maximum time-out	0	120	3	min.	3
FTC	Evaporator fan timed control	NO	YES	YES	flag	YES
FT1	Fan stop delay	0	180	15	sec.	15
FT2	Timed fan stop	0	30	2	min.	2
FT3	Timed fan run	0	30	1	min.	1
ATL	Low alarm differential	-12	0	-5	°K	-5
ATH	High alarm differential	0	12	5	°K	5
ATD	Alarm Temperature Delay	0	120	90	min.	90
AHT	Condenser Alarm Temperature	0	75	60	°C	60
AHM	Condenser high temp. alarm operation	NON; ALR; STP		NON	flag	NON
ACC	Condenser cleaning period	0	52	0	wks	0
HDS	Sensitivity function eco / heavy duty	1	5	3	flag	3
IISM	2nd parameter set switching mode	NON; MAN; HDD; DI2		HDD	flag	HDD
IISL	Minimum 2nd temp. set	-40	IISH	1	°C	1
IISH	Maximum 2nd temp. set	IISL	40	3	°C	3
IISP	Effective 2nd temperature set point	IISL	IISH	1	°C	1
IIHY	Hysteresis 2nd temperature set	0.1	10	3	°K	3
IIFT	Evap. fan timed control in mode 2	NO	YES	NO	flag	NO
IIDF	Defrost Frequency / 24h in mode 2	0	24	4	1/24h	4
SB	Button 0/1 enabling	NO	YES	YES	flag	YES
DS	Door switch enabling	NO	YES	YES	flag	YES
CSD	Compressor stop delay from door opening	0	30	1	min.	1
ADO	Door alarm delay	0	30	8	min.	8
D12	Function digital input D12	NON; HPS; IISM; RDS		NON	flag	NON
LSM	Light switch mode	NON; MAN; DOR		NON	flag	NON
OAU	Control of AUX output	NON; 0-1; LGT; 2CU; 2EU; ALR		NON	flag	NON
OS1	T1 (air) probe offset	-12	12	0	°K	0
T2	T2 (evap.) probe enabling	NO	YES	NO	flag	NO
OS2	T2 (evap.) probe offset	-12	12	0	°K	0
T3	T3 (cond.) probe enabling	NO	YES	NO	flag	NO
OS3	T3 (cond.) probe offset	-12	12	0	°K	0
T4	T4 (aux.) probe enabling	NON; 2CU; 2EU		NON	flag	NON
OS4	T4 (aux.) probe offset	-12	12	0	°K	0
TLD	Delay for min./max. temp storage	1	30	5	min.	5
SIM	Display slowdown	0	100	3	exp.	3
ADR	Unit peripheral address	1	255	1	exp.	1

Parameter list for Wine cabinets including: -
 EPREMG600 (Wine model), EPREMG1350 (Wine model).

Note: For all counters adjust parameter 'DS' to NO as door switches are not fitted to these models.

Mnem.	Definition	Min.	Max	Default	Dim.	WT
SCL	Readout scale	1°C; 2°C; °F		2	flag	2
SPL	Minimum setpoint [I]	-40	SPH	1	°C	8
SPH	Maximum setpoint [I]	SPL	40	3	°C	12
SP	Setpoint [I]	SPL	SPH	2	°C	10
HYS	Thermostat hysteresis [I]	0.1	10	3	°K	2
CRT	Minimum compressor rest time	0	30	2	min.	2
CT1	Compressor run with T1 failure	0	30	7	min.	7
CT2	Compressor stop with T1 failure	0	30	3	min.	3
2CD	Start delay 2nd compressor	0	120	0	sec.	0
DFR	Defrost frequency / 24h	0	24	2	1/24h	4
DLI	Defrost end temperature	-40	40	20	°C	20
DTO	Maximum defrost duration	1	120	20	min.	20
DTY	Defrost type	OFF; ELE; GAS		OFF	flag	OFF
DRN	Drain down time	0	30	2	min.	2
DDY	Defrost display control	0	60	10	min.	10
FID	Fan activity during defrost	NO	YES	YES	flag	YES
FDD	Fan re-start delay temperature	-40	40	0	°C	0
FTO	Evaporator fan maximum time-out	0	120	3	min.	3
FTC	Evaporator fan timed control	NO	YES	YES	flag	YES
FT1	Fan stop delay	0	180	15	sec.	15
FT2	Timed fan stop	0	30	2	min.	2
FT3	Timed fan run	0	30	1	min.	1
ATL	Low alarm differential	-12	0	-5	°K	-5
ATH	High alarm differential	0	12	5	°K	5
ATD	Alarm Temperature Delay	0	120	90	min.	90
AHT	Condenser Alarm Temperature	0	75	60	°C	60
AHM	Condenser high temp. alarm operation	NON; ALR; STP		NON	flag	NON
ACC	Condenser cleaning period	0	52	0	wks	0
HDS	Sensitivity function eco / heavy duty	1	5	3	flag	3
IISM	2nd parameter set switching mode	NON; MAN; HDD; DI2		HDD	flag	HDD
IISL	Minimum 2nd temp. set	-40	IISH	1	°C	1
IISH	Maximum 2nd temp. set	IISL	40	3	°C	3
IISP	Effective 2nd temperature set point	IISL	IISH	1	°C	1
IIHY	Hysteresis 2nd temperature set	0.1	10	3	°K	3
IIFT	Evap. fan timed control in mode 2	NO	YES	NO	flag	NO
IIDF	Defrost Frequency / 24h in mode 2	0	24	4	1/24h	4
SB	Button 0/1 enabling	NO	YES	YES	flag	YES
DS	Door switch enabling	NO	YES	YES	flag	YES
CSD	Compressor stop delay from door opening	0	30	1	min.	1
ADO	Door alarm delay	0	30	8	min.	8
D12	Function digital input D12	NON; HPS; IISM; RDS		NON	flag	NON
LSM	Light switch mode	NON; MAN; DOR		NON	flag	NON
OAU	Control of AUX output	NON; 0-1; LGT; 2CU; 2EU; ALR		NON	flag	NON
OS1	T1 (air) probe offset	-12	12	0	°K	0
T2	T2 (evap.) probe enabling	NO	YES	NO	flag	NO
OS2	T2 (evap.) probe offset	-12	12	0	°K	0
T3	T3 (cond.) probe enabling	NO	YES	NO	flag	NO
OS3	T3 (cond.) probe offset	-12	12	0	°K	0
T4	T4 (aux.) probe enabling	NON; 2CU; 2EU		NON	flag	NON
OS4	T4 (aux.) probe offset	-12	12	0	°K	0
TLD	Delay for min./max. temp storage	1	30	5	min.	5
SIM	Display slowdown	0	100	3	exp.	3
ADR	Unit peripheral address	1	255	1	exp.	1

Technical Data EPrem Cabinets

Model	Gas	Gas Charge	Compressor	Capillary	Defrost Type	Voltage	Power Consumption	Fuse Rating
							kW/48hrs	
EPREM S 400H	R134A	380 grms	FR7.5GX	2.8m x 0.042	Timed Off Cycle	230/50/1	4.2 (indicative)	13 Amp
EPREM S 400L	R404A	360 grms	SC15CL	3.0m x 0.047	Hot Gas	230/50/1	6.2 (indicative)	13 Amp
EPREM G 500H	R134A	380 grms	FR7.5GX	2.8m x 0.042	Timed Off Cycle	230/50/1	4.1 (indicative)	13 Amp
EPREM G 500L	R404A	360 grms	SC15CL	3.0m x 0.047	Hot Gas	230/50/1	6.2 (indicative)	13 Amp
EPREM G 600H	R134A	380 grms	FR7.5GX	2.8m x 0.042	Timed Off Cycle	230/50/1	3.71 (tested)	13 Amp
EPREM G 600M	R134A	380 grms	FR7.5GX	2.8m x 0.042	Hot Gas	230/50/1	5.4 (indicative)	13 Amp
EPREM G 600L	R404A	360 grms	SC15CL	3.0m x 0.047	Hot Gas	230/50/1	14.81 (tested)	13 Amp
EPREM G 1100H	R134A	450 grms	SC15GX	3.0m x 0.054	Timed Off Cycle	230/50/1	7.6 (indicative)	13 Amp
EPREM G 1100L	R404A	660 grms	CAJ2446Z-SE	3.0m x 0.054	Hot Gas	230/50/1	9.0 (indicative)	13 Amp
EPREM G 1350H	R134A	450 grms	SC15GX	3.0m x 0.054	Timed Off Cycle	230/50/1	6.52 (tested)	13 Amp
EPREM G 1350M	R134A	450 grms	SC15GX	3.0m x 0.054	Hot Gas	230/50/1	10 (indicative)	13 Amp
EPREM G 1350L	R404A	660 grms	CAJ2446Z-SE	3.0m x 0.054	Hot Gas	230/50/1	28.76 (tested)	13 Amp
EPREM G 300/300 HL	R134A	320 grms	FR7.5GX	3.0m x 0.042	Timed Off Cycle	230/50/1	10.2 (indicative)	13 Amp
EPREM B 600H	R404A	300 grms	SC15CL	3.0m x 0.042	Electric	230/50/1	3.71 (tested)	13 Amp
	R134A	380 grms	FR7.5GX	2.8m x 0.042	Timed Off Cycle	230/50/1		13 Amp
EPREM B 600L	R404A	360 grms	SC15CL	3.0m x 0.047	Hot Gas	230/50/1	14.81 (tested)	13 Amp
PREM G 600F	R134A	270 grms	FR7.5GX	3.0m x 0.054	Timed Off Cycle	230/50/1	4.8 (indicative)	13 Amp
PREM G 1350F	R134A	360 grms	SC12GX	2.5m x 0.054	Timed Off Cycle	230/50/1	13.16 (indicative)	13 Amp

Technical Data EPrem Counters

Model	Gas	Gas Charge	Compressor	Capillary	Defrost Type	Voltage	Power Consumption	Fuse Rating
							kW/48hrs	
EPREM 1/2H	R134A	360 grms	FR7.5GX	3.0m X 0.042	Timed Off Cycle	230/50/1	3.3 (tested)	13 Amp
EPREM 1/2M	R134A	360 grms	FR7.5GX	3.0m X 0.042	Hot Gas	230/50/1	3.3 (indicative)	13 Amp
EPREM 1/2L	R404A	335 grms	SC 15CL	3.0m X 0.042	Hot Gas	230/50/1	6.4 (indicative)	13 Amp
EPREM 1/3H	R134A	315 grms	FR7.5GX	3.0m X 0.042	Timed Off Cycle	230/50/1	4.7 (indicative)	13 Amp
EPREM 1/3M	R134A	315 grms	FR7.5GX	3.0m X 0.042	Hot Gas	230/50/1	4.7 (indicative)	13 Amp
EPREM 1/3L	R404A	360 grms	SC 15CL	3.0m X 0.042	Hot Gas	230/50/1	23.9 (indicative)	13 Amp
EPREM 1/4H	R134A	370 grms	SC12GX	3.0m X 0.054	Timed Off Cycle	230/50/1	5.2 (indicative)	13 Amp
EPREM 1/4M	R134A	370 grms	SC12GX	3.0m X 0.054	Hot Gas	230/50/1	5.2 (indicative)	13 Amp
EPREM 1/4L	R404A	375 grms	SC 21CLX	3.0m X 0.054	Hot Gas	230/50/1	23.9 (indicative)	13 Amp
EPREM 2/2H	R134A	365 grms	FR7.5GX	3.0m X 0.042	Timed Off Cycle	230/50/1	3.8 (indicative)	13 Amp
EPREM 2/2L	R404A	360 grms	SC 15CL	3.0m X 0.042	Hot Gas	230/50/1	23.9 (indicative)	13 Amp
EPREM 2/3H	R134A	380 grms	SC12GX	3.0m X 0.054	Timed Off Cycle	230/50/1	11.0 (indicative)	13 Amp
EPREM 2/3L	R404A	380 grms	SC 21CLX	3.0m X 0.054	Hot Gas	230/50/1	16.8 (indicative)	13 Amp

Note: The Power Consumption values referred to as tested are to the ECA test standard. Actual power consumption will be greatly affected by ambient temperature, loading, usage and cabinet maintenance.

Technical Data EPrem Cabinets using R290 Refrigerant



Model	Gas	Gas Charge	Compressor	Capillary	Defrost Type	Voltage	Power Consumption	Fuse Rating
							kW/48hrs	
EPREM S 400H	R290	150 grms	TL5CNX	2.8m x 0.042	Timed Off Cycle	230/1/50	4.2 (indicative)	13 Amp
EPREM S 400L	R290	150 grms	SC15CNX	3.0m x 0.042	Hot Gas	230/50/1	6.2 (indicative)	13 Amp
EPREM G 500H	R290	150 grms	TL5CNX	2.8m x 0.042	Timed Off Cycle	230/50/1	3.8 (indicative)	13 Amp
EPREM G 500L	R290	150 grms	SC15CNX	3.0m x 0.042	Hot Gas	230/50/1	13.4 (indicative)	13 Amp
EPREM G 600H	R290	150 grms	TL5CNX	2.8m x 0.042	Timed Off Cycle	230/50/1	3.8 (tested)	13 Amp
EPREM G 600M	R290	150 grms	TL5CNX	2.8m x 0.042	Hot Gas	230/50/1	5.4 (indicative)	13 Amp
EPREM G 600L	R290	150 grms	SC15CNX	3.0m x 0.047	Hot Gas	230/50/1	13.4 (tested)	13 Amp
EPREM G 1100H	R290	200 grms	SC12CNX	3.0m x 0.054	Timed Off Cycle	230/50/1	7.6 (indicative)	13 Amp
EPREM G 1100L	R290	220 grms	MX23FB	3.0m x 0.054	Hot Gas	230/50/1	9.0 (indicative)	13 Amp
EPREM G 1350H	R290	150 grms	SC12CNX	3.0m x 0.054	Timed Off Cycle	230/50/1	5.66 (tested)	13 Amp
EPREM G 1350M	R290	150 grms	SC12CNX	3.0m x 0.054	Hot Gas	230/50/1	9.0 (indicative)	13 Amp
EPREM G 1350L	R290	220 grms	MX23FB	3.0m x 0.054	Hot Gas	230/50/1	25.1 (tested)	13 Amp
EPREM B 600H	R290	150 grms	TL5CNX	2.8m x 0.042	Timed Off Cycle	230/50/1	3.8 (tested)	13 Amp
EPREM B 600L	R290	150 grms	SC15CNX	3.0m x 0.042	Hot Gas	230/50/1	13.4 (tested)	13 Amp
PREM G 600F	R290	150 grms	SC15CNX	3.0m x 0.042	Timed Off Cycle	230/50/1	4.8 (indicative)	13 Amp
PREM G 1350F	R290	140 grms	SC12CNX	2.5m x 0.054	Timed Off Cycle	230/50/1	13.16 (indicative)	13 Amp

Technical Data EPrem Counters using R290 Refrigerant

Model	Gas	Gas Charge	Compressor	Capillary	Defrost Type	Voltage	Power Consumption	Fuse Rating
							kW/48hrs	
EPREM 1/2H	R290	150 grms	TL5CNX	3.0m X 0.042	Timed Off Cycle	230/50/1	3.2 (tested)	13 Amp
EPREM 1/2M	R290	150 grms	TL5CNX	3.0m X 0.042	Hot Gas	230/50/1	3.2 (indicative)	13 Amp
EPREM 1/2L	R290	150 grms	SC15CNX	3.0m X 0.042	Hot Gas	230/50/1	6.4 (indicative)	13 Amp
EPREM 1/3H	R290	150 grms	TL5CNX	3.0m X 0.042	Timed Off Cycle	230/50/1	4.3 (indicative)	13 Amp
EPREM 1/3M	R290	150 grms	TL5CNX	3.0m X 0.042	Hot Gas	230/50/1	4.7 (indicative)	13 Amp
EPREM 1/3L	R290	150 grms	SC15CNX	3.0m X 0.042	Hot Gas	230/50/1	22.8 (indicative)	13 Amp
EPREM 1/4H	R290	150 grms	SC12CNX	3.0m X 0.054	Timed Off Cycle	230/50/1	5.2 (indicative)	13 Amp
EPREM 1/4M	R290	150 grms	SC12CNX	3.0m X 0.054	Hot Gas	230/50/1	5.2 (indicative)	13 Amp
EPREM 2/2H	R290	150 grms	TL5CNX	3.0m X 0.042	Timed Off Cycle	230/50/1	3.8 (indicative)	13 Amp
EPREM 2/2L	R290	150 grms	SC15CNX	3.0m X 0.042	Hot Gas	230/50/1	22.8 (indicative)	13 Amp
EPREM 2/3H	R290	150 grms	SC12CNX	3.0m X 0.054	Timed Off Cycle	230/50/1	11.0 (indicative)	13 Amp

Note: The Power Consumption values referred to as tested are to the ECA test standard. Actual power consumption will be greatly affected by ambient temperature, loading, usage and cabinet maintenance.

Wiring Diagram for High Temperature Models



CUSTOMER COPY


NOTES:
 CONTROLLER CONFIGURED FOR 60V CYCLE SERVICE.
 ALL CABLES 3mm UNLESS STATED

BR - BROWN	BK - BLACK	PK - PINK
BL - BLUE	WH - WHITE	BE - BEIGE
GY - GREEN/YELLOW	GR - GREY	GR - GREEN
RD - RED	VT - VIOLET	CL - CLEAR
OR - ORANGE		



REV	TITLE BLOCK UPDATED	DATE	BY	DWG
03	TITLE BLOCK UPDATED	24/01/2008		
	DESCRIPTION			
	Wiring Diagram	01-281712-00-03		
	EP0001300H-A	Date: 22/08/08	Drawn: ndede	
	INTEGRAL CONFIGURATION	approved:		
		Sheet	of	

Wiring Diagram for Meat and Low Temperature Models




NOTES:

- CONDENSER FAN PROBE FITTED AS AN OPTION.
- DOOR SWITCHES NOT FITTED TO CONDENSER MODELS.
DS2 FITTED TO TWO DOOR CABINET MODELS WIRED IN SERIES TO DS1.
DS2, DS3 AND DS4 FITTED TO FOUR DOOR CABINET MODELS WIRED IN SERIES.
- SECOND EVAPORATOR FAN / MILLION HEATER ONLY FITTED TO LARGER CAPACITY MODELS.
- DRAIN LINE HEATER STANDARD IN LOW TEMPERATURE MODELS.
- OPTIONAL WARMER HEATER CONNECTED DIRECTLY TO CONTROLLER.
- ELECTRIC DEFROST HEATER FITTED INSTEAD OF DEFROST SOLENOID.
- ALL CABLE 1.0mm² UNLESS OTHERWISE STATED.
- DOUBLE INSULATED CABLE: PUG & SOCKET CONNECTION CABLE CONNECTION
- CABLE COLOUR CODE:

BF - BROWN	BD - RED	BY - GREY
BL - BLUE	BB - BLACK	BT - VIOLET
B/Y - GREEN / YELLOW	BH - WHITE	OR - ORANGE

 (ALL EARTH WIRING TO BE GREEN/YELLOW)



CUSTOMER COPY

FOSTER FOSTER REFRIGERATOR (U.K) LTD
 CALDERWOOD ROAD EDINBURGH LEYDOUN ROAD PLEASANTON
 TEL: 0131 627 4000 FAX: 0131 627 4001

DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION

DRAWING NO. - 00-254270-00-04
 SHEET 1 OF 1
 MADE IN U.K.
 DATE: 13/07/06
 CHECKED BY: J. BROWN
 DRAWN BY: M. S.



Foster European Operations

France

Foster Refrigerator France SA

Tel: (33) 01 34 30 22 22. Fax: (33) 01 30 37 68 74.

Email: commercial@fosterfrance.com

Germany

Foster Refrigerator Gmbh,

Tel: (49) 781 990 7840. Fax (49) 781 990 7844.

Email: info@foster-gmbh.de

Foster Refrigerator

Oldmedow Road

Kings Lynn

Norfolk

PE30 4JU

Tel: 0843 216 8833

Fax: 0843 216 4707

Website: www.fosterrefrigerator.co.uk

Email: support@foster-uk.com

a Division of 'ITW (UK) Ltd'

EPREM CAB/COUNT LF28/SM 07/10